

POWERHOUSE® PRO SERIES GENERATOR SPECS

POWERHOUSE PRO SERIES INVERTER GENERATOR SPECIFICATIONS

FEATURE	PH1000i (69270)	PH2100Pri (69271)	PH2700Pri (69272)	PH3100Ri (69273)
SPECIFICATIONS				
AC Output: Rated / Max (Watts)	900 / 1000 W	2000 / 2100 W	2600 / 2700 W	3000 / 3100 W
DC Output (A)	12 V-5 A	12 V-8.3 A	12 V-8.3 A	12 V-8.3 A
Maximum Current (A)	8.3 A	17.5 A	22.5 A	25.8 A
Maximum Engine Speed	5500 rpm	5000 rpm	5000 rpm	3600 rpm
Engine Type	Single Cylinder, 4-Stroke OHV, Air Cooled Gasoline	Single Cylinder, 4-Stroke OHC, Air Cooled Gasoline	Single Cylinder, 4-Stroke OHC, Air-Cooled Gasoline	Single Cylinder, 4-Stroke OHV, Air-Cooled Gasoline
Horsepower (hp) / Displacement	1.63hp / 53cc	4.35hp / 125cc	5.1hp / 150cc	6.8hp / 270cc
Starting System	Recoil	Remote, Electric & Recoil	Remote, Electric & Recoil	Remote, Electric & Recoil
Continuous Run Time (hr), Full load (1/4 load) per Tankful	3.7 hrs. (9.6 hrs.)	3.0 hrs. (7.5 hrs.)	2.9 hrs. (7.2 hrs.)	7.6 hrs. (17.8 hrs.)
Fuel Tank Capacity (Gal)	0.8 gal.	1.3 gal.	1.4 gal.	4.4 gal.
Generator Dimensions (in) (L x W x H)	18-1/8" x 9-13/16" x 15-1/8"	22" x 11" x 19"	22-3/4" x 13" x 17"	23-5/8" x 17-3/4" x 20-1/2"
Dry Weight (lb.)	30.8 lbs.	73 lbs.	80 lbs.	129 lbs.
Noise Level, dB @23': Zero load -Full load	55-64 dB	56-66 dB	58-67 dB	56-65 dB
Rated Current (A)	7.5 A	16.7 A	21.7 A	25 A
Rated Frequency (Hz)	60 Hz	60 Hz	60 Hz	60 Hz
Rated Voltage (V)	120 V	120 V	120 V	120 V
Receptacles	One 120 V, 20 A 5-20R Duplex	One 120 V, 20 A 5-20R Duplex	Two 120V, 20A 5-20R	One 120 V, 20 A 5-20R Duplex & One 120 V, 30 A L5-30R
Fuel Type	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline	Unleaded Gasoline
Oil Capacity	8.5 oz.	15.2 oz.	16 oz.	35 oz.
Oil Type	15W-40	15W-40	15W-40	15W-40
Spark Plug	A7RTC	A7RTC	A7RTC	F7RTC
FEATURES				
Accessories Included	Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Manual, Oil Drain Extension	Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Manual, Keys & Remote, Oil Drain Extension, Spare 10A Glass Tube Fuse		
Automatic Low Oil Shutdown	Yes	Yes	Yes	Yes
Certifications	EPA, CSA, CARB, ISO 9001	EPA, CETL, CARB, ISO 9001	EPA, CETL, CARB, ISO 9001	EPA, CSA, CARB, ISO 9001
Choke	Manual	Auto	Auto	Auto/Elec
Electric Circuit Breaker	Inverter Controlled & Panel Mounted			
Fuel Economy Switch	Yes	Yes	Yes	Yes
Fuel Gauge	No	No	No	Yes
Hour Meter	No	No	No	Yes
Ignition System	Electronic Ignition	Electronic Ignition	Electronic Ignition	Electronic Ignition
Inverter Equipped	Yes	Yes	Yes	Yes
Overload Reset Switch	Yes	Yes	Yes	Yes
Parallel Ready	No	Yes	Yes	No
Phase	Single	Single	Single	Single
Primer Bulb	No	Yes	Yes	No
Remote Control	No	Yes	Yes	Yes
Structure	Enclosed	Enclosed	Enclosed	Enclosed
Wheels	No	No	2 Fixed & Handle	2 Fixed with Brakes, 2 Swivel

POWERHOUSE Wi SERIES INVERTER GENERATOR SPECIFICATIONS

FEATURE	500Wi (60370)	2000Wi (60376)
SPECIFICATIONS		
AC Output: Rated / Max (Watts)	450 / 500 W	1900 / 2000 W
DC Output (A)	12 V–2.5 A	12 V–8.3 A
Maximum Current (A)	4.1 A	16.7 A
Engine Type	Single Cylinder, 4-Stroke OHV, Air Cooled Gasoline	Single Cylinder, 4-Stroke OHV, Air Cooled Gasoline
Horsepower (hp) / Displacement	0.9hp / 31cc	4.3hp / 125cc
Starting System	Recoil	Recoil
Continuous Run Time (hr), Full load (1/4 load) per Tankful	3.5 hrs. (7.5 hrs.)	3.0 hrs. (7.5 hrs.)
Fuel Tank Capacity (Gal)	0.37 gal.	1.4 gal.
Generator Dimensions (in) (L x W x H)	14.1" x 8.2" x 12.6"	22" x 11" x 19"
Dry Weight (lb.)	21.38 lbs.	62 lbs.
Noise Level, dB @23': Zero load –Full load	55–64 dB	56–66 dB
Rated Current (A)	3.75 A	15.8 A
Rated Frequency (Hz)	60 Hz	60 Hz
Rated Voltage (V)	120 V	120 V
Receptacles	One 120 V, 20 A 5-20R Single	One 120 V, 20 A 5-20R Duplex
Fuel Type	Unleaded Gasoline	Unleaded Gasoline
Oil Capacity	7.4 oz.	15.6 oz.
Oil Type	15W-40	15W-40
FEATURES		
Accessories Included	Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Manual, Oil Drain Extension	Oil Jug, 12 V Charge Cable, Spare Spark Plug, Spark Plug Wrench & Handle, Manual, Oil Drain Extension
Automatic Low Oil Shutdown	Yes	Yes
Certifications	EPA, CETL, CARB, ISO 9001	EPA, CSA, CARB, ISO 9001
Choke	Manual	Manual
Electric Circuit Breaker	Inverter Controlled & Panel Mounted	
Fuel Economy Switch	Yes	Yes
Ignition System	Electronic Ignition	Electronic Ignition
Inverter Equipped	Yes	Yes
Overload Reset Switch	No	No
Primer Bulb	No	No
Remote Control	No	No
Structure	Enclosed	Enclosed
Warranty	1 Year Consumer/6 Month Commercial	1 Year Consumer/6 Month Commercial
Wheels	No	No